



Rcstars Industrial (Shenzhen) Co.Ltd

Add.: 7/F, 2nd Bldg., Senyang High-Tech Park, Rd.7, Guangming New District, Shenzhen, China 518106

Toll Free: (86) 400 6655 635 Tel.: +86-755-86299415 Fax: +86-755-26607454

Attn: Yoyo Email : yoyo@rcstarsgroup.com Mob: +8615994822690

15.6Inch High Brightness Window Facing Android Screen



EXW: Configuration 527S, 4+32GB, Android 13 OS + AG & Laminated glass, 5 Screens as 1 Set

Pricing Including: UHP-200-24 power supply + wire rope + ceiling bracket + industrial-grade power adapter + IR remote control + complete set of screws + installation tools

Model No.	RCS-151CAZ (5 Screens as 1 Set)
MOQ 3 Sets	US\$2,035.60
10 Sets	US\$1,980.80
25 Sets	US\$1,882.90
75 Sets	US\$1,740.00
150 Sets	US\$1,686.92

Panel Specifications

Panel model	15.6inch TFT LED
Max Resolution	1920x1080
Aspect Ratio	16:09
Pixel Pitch	0.17925x0.17925
Viewing Angle	85/85/85/85
Contrast Ratio	800:1
Brightness	1500cd/m
Response Time	30ms

PC configuration

Processor	Allwinner A527 octa-core chips
CPU	A527, eight-core, up to 1.8GHz
GPU	ARM G57 MC1 GPU supports OpenGL ES 3.2/2.0/1.1, Vulkan1.1/1.2/1.3, and OpenCL2.2
Memory	LPDDR4 4GB
Flash	32GB
Operation system	Android 13
Network	Wired: Gigabit Ethernet Wi-Fi: Support Wi-Fi 6, 2.4G/5G dual-mode, 802.11 a/b/g/n/ac/ax protocols 4G: PCI-E standard interface, supports 4 PIN external modules;
Bluetooth	Bluetooth 5.4
4G optional	PCI-E standard interface, supports 4 PIN external modules;
Rear Panel I/O	1-channel USB 3.0 TYPE-A HOST, output power 5V 1A 1-channel USB 2.0 TYPE-A OTG, output power 5V 1A 1-way USB-4G 4pin connector, output power 5V 1A 2-way USB 2.0 TYPE-C (USB2.0 HOST) output power 5V 1A (shared with the pin USB port) 1-way USB 2.0 TYPE-C video input, external output power 5V 2A
Video	Support VP9, H.265 4K60, H.264 4K30, (AVS/AVS+, VP8, MPEG1, MPEG2, MPEG4, XVID, H263, Sorenson Spark, MJPEG 1080P)
Image	Support various image formats such as JPG, BMP, PNG, etc.
Audio	Support MP3, OGG, FLAC, APE, AAC, AMR, WAV, DSD, G729, ALAC, ATRAC, OPUS formats
Office	word, Excel,ppt,pdf
Scrolling text	txt
Language	Support multiple languages
System Management	Native Android system, open root permissions, can carry out product customization and development Real-time remote monitoring, self-recovery in case of system crash, 24/7 unattended operation Support OTA remote upgrade; support USB flash drive upgrade Support boot animation definition Support server/stand-alone mode switching Support Wi-Fi hotspot Support software watchdog
System Built-in	Camera, Clock, File Manager, Files, Gallery, HDMI IN, Browser, Settings, Recorder, Video Player
CMS Software	Support remotely controlled through CMS Software
PCB Size(mm)	95X170
PCB Thickness(mm)	1.6mm ± 10%
Screw Hole	φ3.5mm x 4
Working Temp	0-50 degree
Model	RCS-S527

General Info.

Material	CNC aluminum casing + full glass
Color	Black glass + black casing
Mount	Hanging mount
Operating temperature	0-50℃
Storage temperature	0-60℃
Operating Humidity	20%-80%
Storage Humidity	20%-90%
Certification	CE/ROHS/FCC

Remarks:

- The price quoted is based on EXW, not including any comm. or rebate.
- Lead time: 20~25 working days for mass production.
- Payment term: by T/T in advance
- Warranty: 12 months for neutral or OEM brand, 24 months for Rcstars brand products.
- All our products are CE, RoHS & FCC certified.
- Price validity: 30 days