



VISUAL DISPLAY

55 Inch Standing Transparent Kiosk

- **Size:** 55 Inch X2
- **Highest resolution:** 1920 × 1080 line-by-line display
- **Perspective (CR>10):** 178 (horizontal); 178° (vertical)
- **Pigment:** 16.7 M multicolour
- **Luminance:** Luminous surface (inner screen)>300 cd/m²
Highlight (outer screen)>700 cd/m²
- **Contrast ratio:** > 1400: 1
- **Signal response time:** < 8ms
- **Visible area:** 1209.6(W) ×680.4(H) mm
- **Backlighting form:** LCD
- **LCD panel brand:** BOE
- **Backlight life:** > 50,000 hours
- **CPU:** RK3288 Cortex-A9 quad-core processor with a maximum clock speed of 1.6GHz
- **GPU:** GPU Mail-T764
- **Internal storage RAM:** 2G (4G optional)
- **Memory ROM:** 16GB (32GB optional)
- **External extended storage:** TF Card (Supports up to 128GB)
- **Peripheral interface:** USB ×2 、 RJ45 × 1
- **Ethernet:** 10/100M adaptive Ethernet
- **Wifi:** Built-in high-performance USB interface Wi-Fi module supporting IEEE 802.11 b/g/nz
- **Telecontroller:** Standard Infrared Remote Control Receiver and Infrared Receiver Pin Interface
- **Operating system:** Android 11/12/14 version and later
- **Basic software:** Web browsing, online chat, email, e-books, File Explorer, clock, alarm, calculator, recording, and more
- **Functional characteristics:** Remote software control of on/off timing
- **CPU:** J 1900/I3/I5/I7 (optional) Main frequency: 2.0GHz-2.4GHz
- **Internal storage:** DDR3 4G/8G/16/G
- **Memory:** 128GB/256GB/500GB high-speed solid-state drives
- **Display core:** CPU with integrated Intel® HD Graphics high-definition graphics card

- **Joggle:** USB ×4、 HDMI OUT × 1、 VGA OUT× 1、 AUDIO OUT × 1、 MIC IN × 1
- **Ethernet:** Supports 10/100M
- **Wifi:** Supports 802.11 b/g/n Wi-Fi at 2.4GHz
- **3G/4G module (optional):** Supports TDD/FDD/WCDMA/TD-SCDMA/GPRS/GSM/EDGE
- **Optimal Operating system:** WIN10/WIN11
- **Basic software:** Web browsing, online chat, email, e-books, File Explorer, clock, alarm, calculator, recording, and more
- **Functional characteristics:** Remote software control of on/off timing
- **Supported video formats::** Supports AVI (H.264, DIVX, XVID), rm, rmvb,MKV (H.264, DIVX, DIVX, XVID),WMV, MOV, MP4 (H.264, MPEG, DIVX, XVID), FLV (H.263, H.264), TS, 3GP, MPG, and other formats
- **Supported image formats::** Common formats such as BMP, JPEG, PNG, and GIF
- **Supported audio formats::** MP3, WAV, WMA, AAC, 3GP, and other standard formats
- **Volume:** Manage platform settings
- **Auto on/off:** Support
- **Play mode:** Loop, insert, scheduled, and fixed-play modes
- **Power supply specifications:** Input voltage range: AC100V to 240V
- **Pulse power:** 10W ×2
- **Maximum power dissipation:** ≤ 150W
- **Standby power consumption:** ≤ 1W
- **Working temperature:** 0°C ~ 40°C
- **Working humidity:** 10% to 90%, no condensation
- **Storage temperature:** -20°C ~ 60°C
- **External dimensions:** As shown in the size diagram
- **Way to install:** Console mode
- **Carton size:** 2230*240*1060mm
- **Weight:** 72.5KG
- **Remote control/battery:** × 1 set
- **Wifi antenna:** 2 × computer cables / 1 × Android cable
- **Power line:** × 1 root
- **USB:** 2 individual
- **Attaching plug:** Bottom outlet, 1.5 m long, with three-core plug
- **Ship type switch:** Inside (inside the lock)
- **Internet access:** 1 inside the door lock
- **Wi-Fi antenna interface:** 2 Object (built-in or external)





